

Flushometers



Manual toilet flushometer

1.6 gpf K-13516
1.28 gpf K-13517

Manual urinal flushometer

0.125 gpf washout K-13520
0.5 gpf washout K-13519
1.0 gpf washout/siphon-jet K-13518
1.0 gpf blowout K-13522



Tripoint® toilet flushometer

1.6 gpf K-10957
1.28 gpf K-10956

Tripoint urinal flushometer

0.125 gpf washout K-10949
0.5 gpf washout K-10958
1.0 gpf blowout K-10959
1.0 gpf washout K-10960
1.0 gpf siphon-jet K-10961



WAVE toilet flushometer

1.6 gpf K-10674
1.28 gpf K-10673

WAVE urinal flushometer

0.125 gpf washout K-10668
0.5 gpf washout K-10675
1.0 gpf washout/siphon-jet K-10676

Name	Model Number	Retrofit Design Model*	Gallons per Flush					Flush Type	Spud Coupling	WaterSense	ADA	Polished Chrome CP
			0.125	0.5	1.0	1.28	1.6					
Toilet Flushometers												
Manual	K-13516	K-13516-RF					•	Siphon-jet	1½"		•	•
	K-13517	K-13517-RF					•	Siphon-jet	1½"		•	•
Touchless with Tripoint Technology	K-10956	K-10669					•	Siphon-jet	1½"		•	•
	K-10957	K-10962					•	Siphon-jet	1½"		•	•
Touchless with WAVE Technology	K-10673	K-10666					•	Siphon-jet	1½"		•	•
	K-10674	K-10677					•	Siphon-jet	1½"		•	•
Urinal Flushometers												
Manual	K-13518	K-13518-RF			•			Washout/siphon-jet	¾"		•	•
	K-13519	K-13519-RF		•				Washout	¾"		•	•
	K-13520	K-13520-RF	•					Washout	¾"		•	•
	K-13522	K-13522-RF			•			Blowout	1¼"		•	•
Touchless with Tripoint Technology	K-10949		•					Washout	¾"	•	•	•
	K-10958	K-10963		•				Washout	¾"	•	•	•
	K-10959	K-10964			•			Blowout	1¼"		•	•
	K-10960	K-10965			•			Washout	¾"		•	•
	K-10961	K-10966			•			Siphon-jet	¾"		•	•
Touchless with WAVE Technology	K-10668		•					Washout	¾"	•	•	•
	K-10675	K-10678		•				Washout	¾"	•	•	•
	K-10676	K-10679			•			Washout/siphon-jet	¾"		•	•

*Retrofit models require a control stop and vacuum breaker